# Freestanding Timber



#### **Timber Tee Pee**

Posts: 100-150mm Jarrah Hardwood Ring: Mild Steel, no coating, sharps removed Fasteners: M12 HDG Steel Cup-head bolts

#### **Timber Stepped Log**

Log: 250-500mm Jarrah Hardwood Angle, tread and rise: Variable

## **Timber Post Swing - Double - Frame**

Posts and crossbar: 200mm Jarrah Hardwood Fixing plate: Mild Steel, HDG, sharps removed Fasteners: M16 HDG Steel Cup-head bolts

## **Timber Post Swing Single - Frame**

Posts and crossbar: 200mm Jarrah Hardwood Fixing plate: Mild Steel, HDG, sharps removed Fasteners: M16 HDG Steel Cup-head bolts

## **Timber Swing A Frame - Frame**

Posts and crossbar: 200mm Jarrah Hardwood Fasteners: M16 HDG Steel Cup-head bolts

## **Timber Balance Log**

Log: 175–200mm Jarrah Hardwood Stirrups: Mild Steel, HDG, sharps removed Fasteners: 14G Bugle head screws

#### **Timber Stilts**

Log: 150-175mm Jarrah Hardwood Fasteners: M12 HDG cup head bolts

#### **Timber Linear Stilts**

Log: 150-175mm Jarrah Hardwood Fasteners: M12 HDG cup head bolts

#### **Timber Steppers**

Log: 300-500mm dia. Jarrah Hardwood

# **Timber Plank Walk**

Stumps: 300-500mm Jarrah Hardwood Beam: 20x50mm Jarrah Hardwood Fasteners: 14G Buale head screws

## Timber Swing-A-Way - Frame

Posts and crossbar: 200mm Jarrah Hardwood Fasteners: M16 HDG Steel Cup-head bolts

# **Concrete Steppers**

Stepper: 300-500mm dia. cast concrete

#### **Chains**

6mm short link stainless steel chain

# www.forpark.com.au

#### STANDARDS

Complies with relevant Australian Standards including: AS 4685:2021 (P1-6) | AS 4685.0:2017 | AS 4422:2016

\*All information is commercial in confidence and is the property of Forpark Australia. All information is correct as at September 2022. For details regarding Australian standards, warranties, insurances, QA and installation, please contact your local office